


CUSTOMER DATASHEET


Printed: 13/11/2019


Product Management
Transportation Europe

Central Article Code: D06130C17-A Created: 16/05/2012

Local Code: EF2353 Modified: 20/12/2018







Final Outlook D0617-A Approval date 15/05/2012

D		D	n	D	M	I۸	N	C	F	C
	_	•	u		IV		W.	•	_	

Voltage (V): 12 V

C20 (Ah): 235.0 20 h Cranking (A): 1300 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

Vibration: V3 (30Hz+/-2Hz/6g/20h)

Endurance: E3 (144 cycles@50%)

CONTAINER

Type: D06 GREY MEDIUM

Hold Down: B0 H.D. Adapter: No

COVER

Type: Flat/Press GREY MEDIUM

Polarity: ETN 3

Terminals: EN taper post

Terminal Adapter: No SOCI: No Ventilation: Central

Filter: 1 Filter per Vent

Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 518

 Width (mm \pm 2):
 279

 Height (mm \pm 2):
 240

 Total Weight (kg \pm 5%):
 55.60

PLUGS

Type: 2 x VCL Vent GREY MEDIUM

HANDLES

Type: 2 x Rope (Rigid holde BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.