


CUSTOMER DATASHEET


Printed: 16/09/2020


Product Management
Transportation Europe

Central Article Code: G34080M10-A Created: 11/06/2010

Local Code: EJ050C Modified: 03/05/2018







Final Outlook G3410-A Approval date 01/11/2010

PERFORMANCES			CONTAINER			
Voltage (V):	12 V		Type:	G34	BLACK	
C20 (Ah):	50.0	20 h	Hold Down:	B7		
Cranking (A):	800	EN	H.D. Adapter:	No		
Charge:	CHARGED		COVER			
Technology:	Orbital		Type:	Maxxima	Maxxima/Orbital BLACK	
Grid:	Pb-Sn		Polarity:	ETN 1		
			Terminals:	SAE M 3	SAE M 3/8"- 5/16" taper&stud	
			Terminal Adapter	: No	No	
			SOCI:	No		
			Ventilation:	Central 2 Filters		
			Filter:			
STD. DIMENSIONS			Lateral Plug:	No		
Length (mm ± 2):	260		PLUGS			
Width (mm ± 2):	173		Type: 6 x Valve+Cov BLACK			
Height (mm ± 2):	206					
Total Weight (kg ± 5%):	17.90		HANDLES			
, ,			Type: 2 x Integrated BLACK			

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

3/8-5/16 nuts in plastic bag

Degassing Tube:

OTHERS

No

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.