


CUSTOMER DATASHEET


Printed: 10/05/2019


Product Management
Transportation Europe

Central Article Code: D23052C18-A Created: 28/10/2009

Local Code: EL605 Modified: 20/12/2018







Final Outlook C2318-A Approval date 15/01/2010

D	D		n	D	N/	IA	N		ÈΕ	C
_	К	Г	u	Т	IV	ΙН	IN	ı	, $lacksquare$	•

Voltage (V): 12 V

C20 (Ah): 60.0 20 h Cranking (A): 520 EN

Charge: WET

Technology: Vented/Flooded

Grid: Ca/Ca

CONTAINER

Type: D23 BLACK Hold Down: B0

Hold Down: B0 H.D. Adapter: No

COVER

Type: Flat/Screw Integ BLACK

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No SOCI: No

Ventilation: Independent

Filter: No Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 230

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 16.20

PLUGS

Type: 6 x M18 BLACK

HANDLES

ype: 1 x Integrated BLACK

OTHERS

Degassing Tube: No

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.