


CUSTOMER DATASHEET


Printed: 20/01/2020


Product Management
Transportation Europe

Central Article Code: D31065W22-A Created: 14/06/2010

Local Code: ER 450 Modified: 05/03/2019







Final Outlook D3122-A Approval date 15/07/2010

PERFORMANCES			
Voltage (V):	12 V		
C20 (Ah):	95.0	20 h	
Cranking (A):	650	EN	
Charge:	WET		
Technology:	Vented/Flooded		
Grid:	Hybrid		

Type: D31 BLACK
Hold Down: Korean B1

CONTAINER

H.D. Adapter: No

COVER

Type: Flat/Press integ BLUE LIGHT

Polarity: ETN 1

Terminals: EN taper post

Terminal Adapter: No

SOCI: Black SOCI with one ball

Ventilation: Central

Filter: 1 Filter at Right

Lateral Plug: No

STD. DIMENSIONS

 Length (mm \pm 2):
 306

 Width (mm \pm 2):
 173

 Height (mm \pm 2):
 222

 Total Weight (kg \pm 5%):
 21.70

PLUGS

Type: 1 x VCL Vent BLUE LIGHT

HANDLES

Type: 1 x Integrated BLACK

OTHERS

Degassing Tube: Elbow+Tube+Valve

All figures show nominal values. Tolerances are according to EN50342 and applicable European Regulations.

This document includes confidential data, is not contractual and could be changed without notice. Any use, copy or distribution has to be authorised in writing by EXIDE Technologies.