



Handling and Storage

- Can be mounted or stored in any orientation except inverted
- 2-years storage life at 77°F (25°C) without needing to charge. Recharge when the OCV is <12.2V (50% SOC).
- Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for Dangerous Goods) and ICAO (International Civil Aviation Organisation)

Charging and Self-Discharge

| Type of charging curve | IUU |
|--|----------------|
| Charger voltage at 68°F (20°C) | 14.4V to 14.8V |
| Self-discharge per month at 68°F (20°C) | 1.25% |
| Self-discharge per month at 104°F (40°C) | 5% |
| 80% depth of discharge cycles | 400 |
| | |

PDF Generated at https://eu.odysseybattery.com 10/13/2023 08:46:19

Information correct at time of exporting PDF. Please check website for updates.

Technical Data Sheet

ODP-AGM27

(ELT-AGM27)

Battery Type

- Group 27 Absorbed Glass Mat (AGM) battery with Thin Plate Pure Lead (TPPL)
- Massive starting power, rapid recovery, and amazing deep cycling capability
- Advanced dual purpose battery for engine start and deep cycle use

Power and Performance

| Voltage | 12V |
|---|----------------------|
| Pulse (5 second) Hot Cranking Amps (PHCA) | 1500A |
| Cold Cranking Amps (CCA) | 850A |
| HCA | 1150A |
| MCA | 975A |
| 20Hr Nominal Capacity (Ah) | 85Ah |
| 10Hr Nominal Capacity (Ah) | 79Ah |
| Reserve Capacity Minutes | 182 mins |
| Terminal | SAE |
| Torque Spec in-lbs (Nm max) | N/A |
| Internal Resistance (m Ω) | $3.8~\text{m}\Omega$ |
| Short Circuit (A) | 2400A |
| | |

Dimensions and Weight

| Length | 12.5 in / 318 mm |
|-----------------------------|--------------------|
| Width | 6.8 in / 173 mm |
| Height (terminals included) | 8.8 in / 224 mm |
| Height (container) | 8.2 in / 208 mm |
| Weight | 59.7 lbs / 27.1 kg |

Temperature

Operating temperature range $-40^{\circ}\text{F}/-40^{\circ}\text{C}$ to $140^{\circ}\text{F}/+60^{\circ}\text{C}$ Optimum storage temperature $68^{\circ}\text{F}/+20^{\circ}\text{C}$

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

*Cold Start Performance S.A.E J537 Apr 2016



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605, USA Tel: +1-800-964-2837 EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland EnerSys Asia 152 Beach Road #11-08 Gateway East Building Singapore 189721 Tel: +65 6416 4800 Want more info? Scan code to access the ODYSSEY® Battery Literature Library

